

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: **89302128.7**

(51) Int. Cl.4: **C12N 15/00**

(22) Date of filing: **03.03.89**

(30) Priority: **26.03.88 GB 8807271**

(43) Date of publication of application:
25.10.89 Bulletin 89/43

(84) Designated Contracting States:
AT BE CH DE ES FR GB GR IT LI LU NL SE

(71) Applicant: **Preece, Alan William**
Radiotherapy and Oncology Centre Horfield
Road
Bristol BS2 8ED(GB)

Applicant: **Follett, Douglas Harold**
Bristol General Hospital Guinea Street
Bristol BS1 6SP(GB)

(72) Inventor: **Preece, Alan William**
Radiotherapy and Oncology Centre Horfield
Road
Bristol BS2 8ED(GB)

Inventor: **Follett, Douglas Harold**
Bristol General Hospital Guinea Street
Bristol BS1 6SP(GB)

(74) Representative: **Morton, Colin David et al**
Keith W Nash & Co. Pearl Assurance House
90-92 Regent Street
Cambridge CB2 1DP(GB)

(54) **Cell fusion apparatus.**

(57) Cell electrofusion apparatus, for example for the production of hybridomas, comprising a flow-through capillary (14) surrounded by a water-cooled jacket (16) and through which a physiologically normal medium (such as a tissue culture fluid) containing cells is pulsed by a pump driven syringe (28), high voltage pulses being applied to electrodes (18) at opposite ends of the channel, which voltage pulses are of a magnitude and duration such that, taking into account the rate of fluid flow through the capillary and the extraction of heat by the cooling means, the temperature of the cell-containing medium is constrained to remain below the limit at which substantial cell damage occurs.




Fig. 1

EP 0 338 667 A1

Cell Fusion Apparatus

Field of the Invention

This invention relates generally to cell fusion apparatus and more particularly to apparatus for fusing cells by electrofusion, for example, to produce hybridomas.

Background to the invention

Electrofusion is a known technique for causing cell hybridization by the application of a high voltage electric field to cells suspended in an electrically conducting medium. The cells may be brought into mutual contact, for example, to group into long chains often known as pearl chain formations, by means such as the addition to the suspension of polyethylene glycol, or dielectrophoresis or charge modification procedures.

Field strengths required for electrofusion of cells are of the order of 300 to 400 kV/m. At such field strengths, a major relevant factor in the known process, carried out on a batch basis in a fusion chamber, is conductive heating, so that a low conductivity non-physiological supporting medium has necessarily had to be employed to avoid heat damage to the cells, together with non-ionic osmotic compensation, for example achieved by the use of mannitol or sucrose as the suspension medium, because osmotic stress also gives rise to low cell viability.

It is a primary object of this invention to provide improved apparatus for the electrofusion of cells, which apparatus permits a physiologically normal medium, i.e. a medium which is ionically and osmotically normal for cells, to be employed, with a consequent substantial increase in cell viability.

The invention

According to the invention, apparatus for the electrofusion of cells comprises a flow channel of specific flow capacity for passage of cells suspended in a medium, cooling means surrounding the flow channel, electrodes at opposite ends of the flow channel, and a high voltage pulse generating circuit for applying DC voltage pulses to the electrodes while the medium is caused to flow slowly through the flow channel.

In use, the voltage pulses are applied at such a magnitude and at such a repetition rate, in relation to the flow capacity of the flow channel, rate of flow of the medium, and the rate of heat extraction by

the cooling means, that the temperature rise of the cell containing medium is so limited that heat damage to the cells in the medium is substantially avoided.

Thus, the invention resides in a flow-through system with cooling wherein electrofusion is effected with DC voltage pulses defined to bring out a pulsed temperature rise limited to a specific maximum value, preferably 37 degrees C, of the cell containing medium, which may thus be constituted by a physiologically normal medium such as a tissue-culture fluid, with a consequent large improvement in cell viability. The invention enables the application of field strengths of 3 to 4 kV/cm, to a fluid which is ionically and osmotically normal for cells, and the temperature of the medium is limited without flowing the material sufficiently fast to disrupt aggregates of cells by shear forces. In use of the apparatus, cells may be aggregated in small clusters by the addition to the medium of a substance such as an antibody material, lectins, a surface-acting substance such as poly-L-lysine or attachment factors. As the fluid flow through the flow channel is preferably a pulsed flow timed in relation to voltage pulses, aggregation in small clusters is advantageous as compared with grouping in relatively long chains.

The invention lends itself in particular to the production of hybrid cells from spleen cells and myeloma cells, for the purpose of produced monoclonal antibodies.

Description of embodiment

The apparatus in accordance with the invention is exemplified in the accompanying drawings, in which:-

Figure 1 is an elevational view of a practical embodiment; and

Figure 2 is a simplified circuit diagram of a voltage pulse generating circuit.

Figure 1 shows a flow-through cell consisting of upper and lower Teflon (Trade Mark) end blocks 10 which serve to locate, through silicon rubber seals carried by locating members 12, a flow channel 14 in the form of a glass capillary tube. The blocks 10 also serve to clamp in position a circulatory glass water jacket 16, surrounding the flow channel 14, the latter having a wall sufficiently thin to ensure efficient cooling of medium flowing through the channel by heat transfer to the circulating water in the surrounding jacket.

Electrodes 18 are disposed in an electrolyte 20

contained in chambers in the end blocks and separated from inlet/outlet passages 22, 24 in the end blocks 10 by semi-permeable membranes 26.

A 1 ml disposable syringe 28 connects with the inlet/outlet passage 22 in the upper end block 10, and is adapted to be operated by a stepper motor 29 controlled from a timer 30 which in practice is constituted by a computerised control means. The inlet/outlet passage in the lower end block 10 connects with a disposable outlet tip 32, which can deliver samples to a fraction collector 34, for example comprising a 96 well micro-titre plate, advanced under supervision of the computerised control means 30.

A high voltage pulse generating circuit 36 applies DC voltage pulses, of a defined magnitude, duration and frequency, to the electrodes 18, again under supervision of the computerised control means 30.

In use, cooling water is circulated through the glass jacket 16, and cells suspended in tissue-culture fluid are passed through the capillary 14 from the disposable syringe 28 driven by the stepping motor 29. Each step triggers the pulse unit 36, which gives a high voltage (approx. 8Kv) pulse of defined length, applied to the electrodes 18 immersed in the electrolyte 20 contained in end block chambers.

After a group of pulses, the fraction collector 34 moves the microtitre plate to retrieve the pulsed sample. The rate of flow is defined by the removal of heat by the water in the water jacket, and the pulse size is defined by the temperature rise tolerated during the applied field. Both the sample syringe 28 and the outlet tip 32 are sterile disposable units.

In more detail, 1 ml is a suitable volume of cell containing medium (tissue-culture fluid). This is delivered by a syringe pump (stepper motor 29) driving a 1 ml disposable syringe (syringe 28) controlled by a microcomputer and interface (timer 30) to deliver 5 fluid pulses per microlitre. Software derived control pulses are used to control the high voltage pulse generating unit 36 as well as the fraction collector 34.

The syringe 28 and the outlet tip 32 are coupled by the capillary 14, which is conveniently of 0.7 mm diameter with about 18 mm of its 22 mm length surrounded by the water jacket 16. The electrolyte side arms are separated from the medium at the 2 mm diameter end block passages 22, 24 by a cellulose membrane (semi-permeable membrane 26) constituted by standard dialysis membrane "viskin" tubing clamped by threaded hollow Teflon (Trade Mark) plugs screwing into the respective end blocks 10. The electrodes 18 are of platinum and are immersed in a 0.9% NaCl solution. Cooling water at 20 degrees C or less flows

through the cooling jacket 16 at approximately 3 ml/minute. The tissue culture medium (approx. 0.9% NaCl) flowing through the capillary 14 has a resistivity of from 16 to 34 Kohms.

Referring to the mode of use in more detail, the instrument is filled manually with tissue culture fluid using a clean disposable syringe which is clipped into the syringe pump. The syringe is emptied under computer control and refilled with cell suspension (approx. 10^6 cells) from a container placed under the disposable tip. The fluid (1 ml) is pulsed at 2 Hz and drawn in at 8 ul sec^{-1} and redelivered to a microtitre plate at the same rate, re-pulsing the sample on the return path.

Limiting conditions generally applicable to the instrument are as follows:-

Peak voltage = 8 Kv

Pulse length (75% points) = 115 us

Fluid resistivity 0.16 K ohms at 20°C

Peak current = 0.5 amps

Power = 4000 watts

Permitted temperature rise = 17°C

Tube volume = 9 ul

At 1 pulse sec^{-1}

$E = 0.5 \text{ Joules} = 0.12 \text{ Cals}$

$\Delta T \text{ max} = 13^\circ \text{C per pulse}$

Heat transfer can be calculated, but it is assumed that the limiting conditions are the enclosed ends of the tube 14. At 9 ul sec^{-1} flow this segment is flushed clear in approx. 0.2 second. Measurements with erythrocytes in saline show lysis occurring at 5-10Hz and the optimum rate was set at 2 Hz pulse rate and flow at 8 ul sec^{-1} .

Moreover, in preliminary measurements carried out on Mouse myeloma cells X63 Ag8-653 and spleen cells, hybrids were obtained and viability at 5 Hz was 75-80%, and was unaffected by lower pulse rates.

A simplified circuit diagram of the high voltage generating circuit is given in Figure 2. Briefly, a capacitor discharge thyristor chopper with transformer output is used to generate 8 KV, 100us pulses controlled by the microcomputer to give a fixed rate of pulsing for a given flow rate.

The main circuit is a two thyristor chopper with thyristor THY 1 discharging C_{10} into the output transformer primary but being forcibly commutated off by THY 2. The circuit is arranged so that both thyristor cathodes are at zero volts and no gate trigger isolation is needed.

On applying mains voltage via rectifying circuit 40, C_{10} is charged to 450V and 5V is provided for the logic circuits. THY 1 anode is then at +450V since C_{10} negative is connected (for DC) to zero volts via T2 primary. When MONO 1 is triggered by the MANUAL button or an external trig pulse, a positive gate signal 75-100 us long (as determined by R2C2) is applied to THY 1 gate via VT 1.

THY 1 then conducts and a 450V negative step is applied to T2 primary. The same step appears on C9: D5 conducts and C9 with L rings for one half cycle leaving THY 2 anode about 200-300 V positive, with C9 charged to about 800 V.

At the end of the 75-100 us period, MONO 2 is triggered by MONO 1 Q output trailing edge and fires THY 2 via VT 2. The load current is diverted through THY 2 and C9 long enough to allow THY 1 to turn off. C9 then continues to discharge through THY 2 and T2 forming the trailing edge of the output pulse.

It is to be noted that rise and fall times at the output are limited at nominal max load of 0.5 A to about 30-40 us by leakage inductance of T2. However, this does result in a short-circuit on T2 secondary only giving peak primary currents about 80 amps, just within the thyristor ratings. R5-C5, R3-C4 isolate gate current from the +5 supply and also help to prevent any later mis-firings following the main pulse, whilst D6 protects THY 1 from reverse voltage and D7 clips overshoot on T2.

R₁₁ is selected to obtain +450V initially on C₁₀, whilst R₂ is selected for the required pulse length.

The complete unit includes a relay dump (not shown) and power supply generating circuits (also not shown).

In a practical embodiment, the instrument and controlling units will preferably be housed in an electrically interlocked cabinet, since it is well suited to fully automatic operation.

Various modifications of the above-described and illustrated embodiment are possible within the scope of the invention as defined by the appended claims.

Claims

1. Apparatus for the electrofusion of cells comprising a flow channel of specific flow capacity for passage of cells suspended in a medium, cooling means surrounding the flow channel, electrodes at opposite ends of the flow channel, and a high voltage pulse generating circuit for applying DC voltage pulses to the electrodes while the medium is caused to flow slowly through the flow channel.

2. Apparatus according to claim 1, in which the applied voltage pulses are of such a magnitude and at such a repetition rate, in relation to the flow capacity of the flow channel, the rate of flow of the medium and the rate of heat extraction by the cooling means, that the temperature rise of the cell containing medium is so limited that heat damage to the cell containing medium is substantially avoided.

3. Apparatus according to claim 1 or claim 2, in which a controlling means for the apparatus limits the temperature of the cell containing medium to 37 degrees C maximum.

4. Apparatus according to claim 1 or claim 2 or claim 3, in which the medium is tissue-culture fluid.

5. Apparatus according to any of claims 1 to 4, in which the peak magnitude of the applied voltage pulses is approximately 8 kV, and said applied voltage pulses have a duration of approximately 100 us at a frequency not exceeding 10 Hz for a flow rate of the cell-containing medium of approximately 10 ul/sec.

6. Apparatus according to any of claims 1 to 5, in which the flow channel is of less than 1 mm diameter with a length of about 20 mm surrounded by the cooling means.


7. Apparatus according to any of claims 1 to 6, in which the cooling means is a circulatory water jacket.

8. Apparatus according to any of claims 1 to 7, in which the flow channel is mounted between end blocks containing inlet/outlet passages communicating with said flow channel, the said respective inlet/outlet passages connecting at one end block with a syringe adapted to be driven by a stepper motor for producing a pulsed flow of the medium and at the other end with an outlet tip for feeding samples into a fraction collector.

9. Apparatus according to claim 8, in which the electrodes are accommodated in electrolyte contained in electrolyte chambers formed in the respective end blocks, the electrolyte being separated from the inlet/outlet passages in the end blocks by semi-permeable membranes.

10. Apparatus according to any of claims 1 to 9, in which the high voltage pulse generating circuit comprises a thyristor chopper for controlling a capacitor discharging into the primary winding of an output transformer, and a triggerable control circuit for the thyristors.

11. Apparatus according to claim 10 when appendant to claim 8 or claim 9, including a computer for supplying first controlling pulses for triggering the control circuit high voltage pulse generator circuit and second controlling pulses, in timed relationship to the first controlling pulses, for triggering a control circuit for the stepper motor.

*Fig. 1*




Fig. 2



| DOCUMENTS CONSIDERED TO BE RELEVANT | | | |
|---|--|--|---|
| Category | Citation of document with indication, where appropriate, of relevant passages | Relevant to claim | CLASSIFICATION OF THE APPLICATION (Int. Cl.4) |
| A | EP-A-0 126 389 (KERFORSCHUNGSANLAGE JÜLICH GESELLSCHAFT MIT BESCHRÄNKTER HAFTUNG) * Figure 5; page 18, lines 12-20 * --- | 1-4 | C 12 N 15/02 |
| A | US-A-4 561 961 (G.A. HOFFMANN) * Claims; figures; column 3, line 55 - column 4, line 15 * --- | 1-3 | |
| A | GB-A- 845 743 (GENERAL ELECTRIC CIE LTD) ----- | | |
| | | | TECHNICAL FIELDS SEARCHED (Int. Cl.4) |
| | | | C 12 N |
| The present search report has been drawn up for all claims | | | |
| Place of search THE HAGUE | | Date of completion of the search 30-05-1989 | Examiner COUCKE A.O.M. |
| <div>CATEGORY OF CITED DOCUMENTS</div> <div><div>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</div><div>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</div></div> | | | |

PUB-NO: EP000338667A1
DOCUMENT-IDENTIFIER: EP 338667 A1
TITLE: Cell fusion apparatus.
PUBN-DATE: October 25, 1989

INVENTOR-INFORMATION:

| NAME | COUNTRY |
|----------------------|---------|
| PREECE, ALAN WILLIAM | N/A |

ASSIGNEE-INFORMATION:

| NAME | COUNTRY |
|------------------------|---------|
| PREECE ALAN WILLIAM | GB |
| FOLLETT DOUGLAS HAROLD | GB |

APPL-NO: EP89302128
APPL-DATE: March 3, 1989

PRIORITY-DATA: GB08807271A (March 26, 1988)

INT-CL (IPC): C12N015/00

EUR-CL (EPC): C12N015/02 , C12N013/00

US-CL-CURRENT: 435/285.2 , 435/286.1

ABSTRACT:

Cell electrofusion apparatus, for example for the production of hybridomas, comprising a flow-through capillary (14) surrounded by a

water-cooled jacket (16) and through which a physiologically normal medium (such as a tissue culture fluid) containing cells is pulsed by a pump driven syringe (28), high voltage pulses being applied to electrodes (18) at opposite ends of the channel, which voltage pulses are of a magnitude and duration such that, taking into account the rate of fluid flow through the capillary and the extraction of heat by the cooling means, the temperature of the cell-containing medium is constrained to remain below the limit at which substantial cell damage occurs.